



Quick Reference Guide

(Owner's manual and full use instructions available on HippLock.com)

**** The HippLock must be inspected prior to each use ****

FAILURE TO FOLLOW ALL INSTRUCTIONS CAN LEAD TO FATAL INJURY

HIPPLOCK INSTALLATION & USE - GABLE ROOF STRUCTURE

1. Inspect the HippLock, ensure there are no defects or loose fasteners prior to use.
2. Attach the pole system to the HippLock device.
3. Attach the safety line to the HippLock.
4. Hang the HippLock on the house gutter, roof, or ladder ensuring no damage occurs to inspected property. (Do not climb the ladder or roof with the HippLock in hand).
5. Climb the ladder, secure the ladder to the gutter for safety.
6. The HippLock is to be used on a roof pitch of 8/12 up to 12/12 pitch. Do not use on pitch readings outside the range.
7. Turn the HippLock upside down (wheels down on roof surface), push HippLock to ridge cap.
8. Rotate the HippLock over the ridge cap (wheels up). Pull on the pole or safety line to ensure the HippLock is securely in place over the ridge cap.
9. Attach the safety line to your safety harness.
10. Dismount the ladder and step onto the roof surface. (Remain directly behind the HippLock while ascending the roof).
11. Once you reach the ridge cap (DO NOT PULL UP ON THE SAFETY LINE AS THIS WILL PULL THE HIPBLOCK UP AND OFF THE RIDGE CAP) install (4) 3/8 inch lag bolts (not included) to secure the HippLock to the roof. (Failure to fasten the HippLock to the roof structure can result in fatal injury).
12. The HippLock is now ready for use on a Gable Type roof. NOTE: The safety line should be attached to the eye hole that is on the same slope of the roof you will be working on.





Quick Reference Guide

(Owner's manual and full use instructions available on HippLock.com)

**** The HippLock must be inspected prior to each use ****

FAILURE TO FOLLOW ALL INSTRUCTIONS CAN LEAD TO FATAL INJURY

REMOVAL OF HIPBLOCK FROM ROOF



1. Remove the four 3/8" lag bolts that attach the HippLock to the roof.
2. Seal the holes in the roof left by the four 3/8" lag bolts with an approved roofing sealant.
3. Attach the safety line to the HippLock on the side you are descending the roof (remain directly behind the HippLock during the transition to the ladder).
4. Ensure your safety line is attached to the HippLock on the same side as you are descending the roof (remain directly behind the HippLock during the transition to the ladder).
5. Rotate the HippLock so that the wheels are now in contact with the roof surface.
6. Using the pole system, descend the HippLock down the roof surface and hang off the gutter, roof, or ladder. (DO NOT descend the ladder or roof with the HippLock in hand)
7. Descend the ladder and remove the HippLock from the gutter, roof, or ladder.

